

SIM ROLL



APPLICATION

As one of our premier putting surfaces, this product is ideal for putting, short chip shots, and indoor golf facilities. The speed of the green will depend on the installation method. This product can be installed indoors or outdoors on concrete or a compacted aggregate base.

PROPERTY	DESCRIPTION
Primary Yarn Polymer	Nylon
Yarn Cross Section	Texturized Nylon
Standard Colors	Forest Green/Verde Lime
Coating Type(s)	Greenback or Natural Rubber
Perforations	No
Pile Height	3/8"
Total Fabric Weight	84 oz/yd ²
Fabric Width	15 ft.
Yarn Shape	



Texturized



SIM ROLL

FINISHED FABRIC	ENGLISH SYSTEM		METRIC SYSTEM		ASTM TEST F-1551
<i>Nominal Specification</i>	Value	Units	Value	Units	<i>Method</i>
Pile Height (Nominal)	.375	In.	9.53	mm.	D-5823
Face Weight	36	oz/yd ²	1221	g/m ²	D-5848
Total Fabric Weight	84	oz/yd ²	2848	g/m ²	D-5848
Primary backing Weight	7	oz/yd ²	237	g/m ²	D-5848
Secondary Coating Weight	41	oz/yd ²	1390	g/m ²	D-5848
Tuft Bind	>8	lbs.	>3.6	Kg.	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	Kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
Total Yarn Linear Density	4,400	Denier	4,889	D-Tex	D-1577
Tensile Strength	8.0	lbs.	3.63	Kg.	D-5034
Stitch Rate	28	Per 3"	71.12	Per 10 cm	D-5793
Machine Gauge	0.1875	In.	0.48	Cm.	D-5793
Flammability	TEST	PASSED	TEST	PASSED	D-2859
Water Permeability w/infill	>30	In./Hr.	>76	Cm./Hr.	F-1551
Fiber Thickness	3.9	mils	100	microns	D-3218
Fabric Width	15	Ft.	4.6	M	None

